



20 Lancaster Street Ingleburn, NSW 2565 Australia, Freecall 1800 761 761. For further Product Information visit [www.eric.com.au](http://www.eric.com.au)

## 510-520 Traditional Pre Cat Lacquer

### Evic Group

Chemwatch Hazard Alert Code: 4

Chemwatch: 5667-86

Version No: 2.1

Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Issue Date: 31/05/2024

Print Date: 03/06/2024

S.GHS.AUS.EN.RISK

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### Product Identifier

Product name	510-520 Traditional Pre Cat Lacquer
Chemical Name	Not Applicable
Synonyms	510,520-15,520-30,520-60,520-Gloss
Proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Chemical formula	Not Applicable
Other means of identification	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	A catalysed sealer for timber. Use according to manufacturer's directions.
--------------------------	---

#### Details of the manufacturer or supplier of the safety data sheet

Registered company name	Evic Group
Address	20 Lancaster Street Ingleburn NSW 2565 Australia
Telephone	1800 761 761
Fax	Not Available
Website	<a href="http://www.eric.com.au/">http://www.eric.com.au/</a>
Email	info@eric.com.au

#### Emergency telephone number

Association / Organisation	Evic Group	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	1800 761 761	+61 1800 951 288
Other emergency telephone numbers	Not Available	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

### SECTION 2 Hazards identification

#### Classification of the substance or mixture

Poisons Schedule	S5
Classification <sup>[1]</sup>	Flammable Liquids Category 2, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Reproductive Toxicity Category 1B, Specific Target Organ Toxicity - Repeated Exposure Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 3, Hazardous to the Aquatic Environment Long-Term Hazard Category 3 <i>*LIMITED EVIDENCE</i>
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

#### Label elements

Hazard pictogram(s)	
Signal word	Danger

**Hazard statement(s)**

<b>H225</b>	Highly flammable liquid and vapour.
<b>H319</b>	Causes serious eye irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H360FD</b>	May damage fertility. May damage the unborn child.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>AUH066</b>	Repeated exposure may cause skin dryness and cracking.

\*LIMITED EVIDENCE

**Precautionary statement(s) Prevention**

<b>P201</b>	Obtain special instructions before use.
<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P260</b>	Do not breathe mist/vapours/spray.
<b>P271</b>	Use only outdoors or in a well-ventilated area.

**Precautionary statement(s) Response**

<b>P308+P313</b>	IF exposed or concerned: Get medical advice/ attention.
<b>P370+P378</b>	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P312</b>	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.

**Precautionary statement(s) Storage**

<b>P403+P235</b>	Store in a well-ventilated place. Keep cool.
<b>P405</b>	Store locked up.

**Precautionary statement(s) Disposal**

<b>P501</b>	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
-------------	--

**SECTION 3 Composition / information on ingredients****Substances**

See section below for composition of Mixtures

**Mixtures**

CAS No	%[weight]	Name
141-78-6	10-30	<u>ethyl acetate</u>
64742-95-6.	10-30	<u>naphtha petroleum light aromatic solvent</u>
123-86-4	10-30	<u>n-butyl acetate</u>
9004-70-0	10-30	<u>nitrocellulose</u>
67-64-1	10-30	<u>acetone</u>
1330-20-7	<5	<u>xylene</u>
64-17-5	<5	<u>ethanol</u>
71-36-3	<5	<u>n-butanol</u>
14807-96-6	<5	<u>talc</u>
110-30-5	<5	<u>N,N'-ethylenebisstearamide</u>
117-81-7	<5	<u>di-sec-octyl phthalate</u>
68002-18-6	<5	<u>urea formaldehyde resin, isobutylated</u>
50-00-0	<1	<u>formaldehyde</u>
Not Available	balance	Ingredients determined not to be hazardous

**Legend:** 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; \* EU IOELVs available

**SECTION 4 First aid measures****Description of first aid measures**

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul> <p>For thermal burns:</p>

Continued...

	<ul style="list-style-type: none"> <li>▶ Decontaminate area around burn.</li> <li>▶ Consider the use of cold packs and topical antibiotics.</li> </ul> <p>For first-degree burns (affecting top layer of skin)</p> <ul style="list-style-type: none"> <li>▶ Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides.</li> <li>▶ Use compresses if running water is not available.</li> <li>▶ Cover with sterile non-adhesive bandage or clean cloth.</li> <li>▶ Do NOT apply butter or ointments; this may cause infection.</li> <li>▶ Give over-the counter pain relievers if pain increases or swelling, redness, fever occur.</li> </ul> <p>For second-degree burns (affecting top two layers of skin)</p> <ul style="list-style-type: none"> <li>▶ Cool the burn by immerse in cold running water for 10-15 minutes.</li> <li>▶ Use compresses if running water is not available.</li> <li>▶ Do NOT apply ice as this may lower body temperature and cause further damage.</li> <li>▶ Do NOT break blisters or apply butter or ointments; this may cause infection.</li> <li>▶ Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape.</li> </ul> <p>To prevent shock: (unless the person has a head, neck, or leg injury, or it would cause discomfort):</p> <ul style="list-style-type: none"> <li>▶ Lay the person flat.</li> <li>▶ Elevate feet about 12 inches.</li> <li>▶ Elevate burn area above heart level, if possible.</li> <li>▶ Cover the person with coat or blanket.</li> <li>▶ Seek medical assistance.</li> </ul> <p>For third-degree burns Seek immediate medical or emergency assistance. In the mean time:</p> <ul style="list-style-type: none"> <li>▶ Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not leave lint in wound.</li> <li>▶ Separate burned toes and fingers with dry, sterile dressings.</li> <li>▶ Do not soak burn in water or apply ointments or butter; this may cause infection.</li> <li>▶ To prevent shock see above.</li> <li>▶ For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway.</li> <li>▶ Have a person with a facial burn sit up.</li> <li>▶ Check pulse and breathing to monitor for shock until emergency help arrives.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor, without delay.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>▶ Urgent hospital treatment is likely to be needed.</li> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Transport to hospital or doctor without delay.</li> </ul>

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5 Firefighting measures****Extinguishing media**

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

**Special hazards arising from the substrate or mixture**

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

**Advice for firefighters**

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ When silica dust is dispersed in air, firefighters should wear inhalation protection as hazardous substances from the fire may be adsorbed on the silica particles.</li> <li>▶ When heated to extreme temperatures, (&gt;1700 deg.C) amorphous silica can fuse.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Liquid and vapour are highly flammable.</li> <li>▶ Severe fire hazard when exposed to heat, flame and/or oxidisers.</li> <li>▶ Vapour may travel a considerable distance to source of ignition.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> </ul> <p>Combustion products include:</p> <p>carbon dioxide (CO<sub>2</sub>)</p> <ul style="list-style-type: none"> <li>▶ When silica dust is dispersed in air, firefighters should wear inhalation protection as hazardous substances from the fire may be adsorbed on the silica particles.</li> <li>▶ When heated to extreme temperatures, (&gt;1700 deg.C) amorphous silica can fuse.</li> </ul> <p>nitrogen oxides (NO<sub>x</sub>) silicon dioxide (SiO<sub>2</sub>) other pyrolysis products typical of burning organic material.</p>
<b>HAZCHEM</b>	•3YE

**SECTION 6 Accidental release measures**

**Personal precautions, protective equipment and emergency procedures**

See section 8

**Environmental precautions**

See section 12

**Methods and material for containment and cleaning up**

<b>Minor Spills</b>	<p>Environmental hazard - contain spillage.</p> <ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> </ul>
<b>Major Spills</b>	<p>Environmental hazard - contain spillage.</p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

**SECTION 7 Handling and storage****Precautions for safe handling**

<b>Safe handling</b>	<ul style="list-style-type: none"> <li>▶ Containers, even those that have been emptied, may contain explosive vapours.</li> <li>▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> <li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Store in original containers in approved flame-proof area.</li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ <b>DO NOT store in pits, depression, basement or areas where vapours may be trapped.</b></li> <li>▶ Keep containers securely sealed.</li> </ul>

**Conditions for safe storage, including any incompatibilities**

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Packing as supplied by manufacturer.</li> <li>▶ Plastic containers may only be used if approved for flammable liquid.</li> <li>▶ Check that containers are clearly labelled and free from leaks.</li> <li>▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> <li>▶ For materials with a viscosity of at least 2680 cSt. (23 deg. C)</li> <li>▶ For manufactured product having a viscosity of at least 250 cSt.</li> </ul>
<b>Storage incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Avoid oxidising agents, acids, acid chlorides, acid anhydrides, chloroformates.</li> <li>▶ Avoid strong acids, bases.</li> </ul>

**SECTION 8 Exposure controls / personal protection****Control parameters****Occupational Exposure Limits (OEL)****INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	ethyl acetate	Ethyl acetate	200 ppm / 720 mg/m3	1440 mg/m3 / 400 ppm	Not Available	Not Available
Australia Exposure Standards	n-butyl acetate	n-Butyl acetate	150 ppm / 713 mg/m3	950 mg/m3 / 200 ppm	Not Available	Not Available
Australia Exposure Standards	acetone	Acetone	500 ppm / 1185 mg/m3	2375 mg/m3 / 1000 ppm	Not Available	Not Available
Australia Exposure Standards	xylene	Xylene (o-, m-, p- isomers)	80 ppm / 350 mg/m3	655 mg/m3 / 150 ppm	Not Available	Not Available
Australia Exposure Standards	ethanol	Ethyl alcohol	1000 ppm / 1880 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	n-butanol	n-Butyl alcohol	Not Available	Not Available	50 ppm / 152 mg/m3	Not Available
Australia Exposure Standards	talca	Talc, (containing no asbestos fibres)	2.5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	di-sec-octyl phthalate	Di-sec-octyl phthalate	5 mg/m3	10 mg/m3	Not Available	Not Available
Australia Exposure Standards	formaldehyde.	Formaldehyde	1 ppm / 1.2 mg/m3	2.5 mg/m3 / 2 ppm	Not Available	Not Available

**Emergency Limits**

Ingredient	TEEL-1	TEEL-2	TEEL-3
ethyl acetate	1,200 ppm	1,700 ppm	10000** ppm
naphtha petroleum, light aromatic solvent	1,200 mg/m3	6,700 mg/m3	40,000 mg/m3
n-butyl acetate	Not Available	Not Available	Not Available

Continued...

Ingredient	TEEL-1	TEEL-2	TEEL-3
acetone	Not Available	Not Available	Not Available
xylene	Not Available	Not Available	Not Available
ethanol	Not Available	Not Available	15000* ppm
n-butanol	60 ppm	800 ppm	8000** ppm
di-sec-octyl phthalate	10 mg/m3	1,000 mg/m3	6,100 mg/m3
formaldehyde.	Not Available	Not Available	Not Available


Ingredient	Original IDLH	Revised IDLH
ethyl acetate	2,000 ppm	Not Available
naphtha petroleum, light aromatic solvent	Not Available	Not Available
n-butyl acetate	1,700 ppm	Not Available
nitrocellulose	Not Available	Not Available
acetone	2,500 ppm	Not Available
xylene	900 ppm	Not Available
ethanol	3,300 ppm	Not Available
n-butanol	1,400 ppm	Not Available
talc	1,000 mg/m3	Not Available
N,N'-ethylenebisstearamide	Not Available	Not Available
di-sec-octyl phthalate	5,000 mg/m3	Not Available
urea formaldehyde resin, isobutylated	Not Available	Not Available
formaldehyde.	20 ppm	Not Available

#### Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
N,N'-ethylenebisstearamide	E	≤ 0.01 mg/m <sup>3</sup>
urea formaldehyde resin, isobutylated	E	≤ 0.1 ppm

**Notes:** Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

#### Exposure controls

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p>
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.</li> </ul>
<b>Skin protection</b>	See Hand protection below
<b>Hands/feet protection</b>	<ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p>For esters:</p> <ul style="list-style-type: none"> <li>▶ Do NOT use natural rubber, butyl rubber, EPDM or polystyrene-containing materials.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care.</p>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ PVC Apron.</li> <li>▶ PVC protective suit may be required if exposure severe.</li> <li>▶ Eyewash unit.</li> <li>▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</li> <li>▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</li> <li>▶ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds.</li> </ul>

#### Recommended material(s)

#### GLOVE SELECTION INDEX

#### Respiratory protection

Type BAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 &

Continued...

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

510-520 Traditional Pre Cat Lacquer

Material	CPI
BUTYL	C
BUTYL/NEOPRENE	C
CPE	C
HYPALON	C
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
NITRILE+PVC	C
PE	C
PE/EVAL/PE	C
PVA	C
PVC	C
PVDC/PE/PVDC	C
SARANEX-23	C
SARANEX-23 2-PLY	C
TEFLON	C
VITON	C
VITON/BUTYL	C
VITON/CHLOROBUTYL	C
VITON/NEOPRENE	C

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	BAX-AUS P2	-	BAX-PAPR-AUS / Class 1 P2
up to 50 x ES	-	BAX-AUS / Class 1 P2	-
up to 100 x ES	-	BAX-2 P2	BAX-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## SECTION 9 Physical and chemical properties

### Information on basic physical and chemical properties

<b>Appearance</b>	Translucent highly flammable liquid with solvent odour; does not mix with water.		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	0.90-0.95
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	Not Applicable	<b>Decomposition temperature (°C)</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Applicable	<b>Viscosity (cSt)</b>	108.108
<b>Initial boiling point and boiling range (°C)</b>	Not Available	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	Not Available	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Not Available	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Available	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	Not Available	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	Not Available	<b>Gas group</b>	Not Available
<b>Solubility in water</b>	Immiscible	<b>pH as a solution (1%)</b>	Not Applicable
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	Not Available

## SECTION 10 Stability and reactivity

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	▶ Unstable in the presence of incompatible materials.

Continued...

	<ul style="list-style-type: none"> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 Toxicological information

### Information on toxicological effects

<b>Inhaled</b>	<p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> <p>Inhalation hazard is increased at higher temperatures.</p> <p>Inhaling high concentrations of mixed hydrocarbons can cause narcosis, with nausea, vomiting and lightheadedness. Low molecular weight (C2-C12) hydrocarbons can irritate mucous membranes and cause incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and stupor.</p> <p>Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.</p> <p>There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.</p>
<b>Ingestion</b>	Accidental ingestion of the material may be damaging to the health of the individual.
<b>Skin Contact</b>	<p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.</p> <p>Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.</p> <p>There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>
<b>Eye</b>	This material can cause eye irritation and damage in some persons.
<b>Chronic</b>	<p>This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.</p> <p>Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material.</p> <p>Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material.</p> <p>Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.</p> <p>Based on experience with animal studies, exposure to the material may result in toxic effects to the development of the foetus, at levels which do not cause significant toxic effects to the mother.</p> <p>Exposure to phthalates over years leads to pain, numbness and spasms in the hands and feet. Many people have developed multiple disorders in the nervous system and the balancing system.</p> <p>Amorphous silicas generally are less hazardous than crystalline silicas, but the former can be converted to the latter on heating and subsequent cooling. Inhalation of dusts containing crystalline silicas may lead to silicosis, a disabling lung disease that may take years to develop.</p> <p>Oral exposure of rats to isobutanol caused cancers of the gullet and stomach, liver or blood (myelogenous leukaemia). Abnormal non-cancer growths were also more common in those animals exposed to isobutanol.</p> <p>Prolonged exposure to ethanol may cause damage to the liver and cause scarring. It may also worsen damage caused by other agents.</p> <p>Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.</p> <p>Soluble silicates do not exhibit sensitizing potential. Testing in bacterial and animal experiments have not shown any evidence of them causing mutations or birth defects.</p> <p>di-sec-octyl phthalate may not cause any adverse effects at low doses, but higher doses may produce growth retardation and increased weight of the liver and kidney, and liver cancers. It can cause testicular damage and skeletal abnormalities to the developing foetus, according to animal testing.</p> <p>Women exposed to xylene in the first 3 months of pregnancy showed a slightly increased risk of miscarriage and birth defects. Evaluation of workers chronically exposed to xylene has demonstrated lack of genetic toxicity.</p> <p>Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.</p>

510-520 Traditional Pre Cat Lacquer	TOXICITY	IRRITATION
	Not Available	Not Available
ethyl acetate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >18000 mg/kg <sup>[2]</sup>	Eye (human): 400 ppm
	Inhalation(Mouse) LC50; >18 mg/l4h <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
Oral (Mouse) LD50; 4100 mg/kg <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
naphtha petroleum, light aromatic solvent	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >1900 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Inhalation (Rat) LC50: >4.42 mg/L4h <sup>[1]</sup>	Skin: adverse effect observed (irritating) <sup>[1]</sup>
Oral (Rat) LD50: >4500 mg/kg <sup>[1]</sup>		
n-butyl acetate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 3200 mg/kg <sup>[2]</sup>	Eye ( human): 300 mg * [PPG]
	Inhalation (Rat) LC50: 0.74 mg/l4h <sup>[2]</sup>	Eye (rabbit): 20 mg (open)-SEVERE
Oral (Rabbit) LD50; 3200 mg/kg <sup>[2]</sup>	Eye (rabbit): 20 mg/24h - moderate	

		Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
		Skin (rabbit): 500 mg/24h-moderate
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
nitrocellulose	<b>TOXICITY</b>	<b>IRRITATION</b>
	Oral (Rat) LD50: >5000 mg/kg <sup>[2]</sup>	Not Available
acetone	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 20000 mg/kg <sup>[2]</sup>	Eye (human): 500 ppm - irritant
	Inhalation(Mouse) LC50; 44 mg/L4h <sup>[2]</sup>	Eye (rabbit): 20mg/24hr -moderate
	Oral (Rat) LD50: 5800 mg/kg <sup>[2]</sup>	Eye (rabbit): 3.95 mg - SEVERE
		Eye: adverse effect observed (irritating) <sup>[1]</sup>
		Skin (rabbit): 500 mg/24hr - mild
	Skin (rabbit):395mg (open) - mild	
	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
xylene	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: >1700 mg/kg <sup>[2]</sup>	Eye (human): 200 ppm irritant
	Inhalation (Rat) LC50: 5000 ppm4h <sup>[2]</sup>	Eye (rabbit): 5 mg/24h SEVERE
	Oral (Mouse) LD50; 2119 mg/kg <sup>[2]</sup>	Eye (rabbit): 87 mg mild
		Eye: adverse effect observed (irritating) <sup>[1]</sup>
	Skin (rabbit):500 mg/24h moderate	
	Skin: adverse effect observed (irritating) <sup>[1]</sup>	
ethanol	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 17100 mg/kg <sup>[1]</sup>	Eye (rabbit): 500 mg SEVERE
	Inhalation (Rat) LC50: 64000 ppm4h <sup>[2]</sup>	Eye (rabbit):100mg/24hr-moderate
	Oral (Rat) LD50: 7060 mg/kg <sup>[2]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>
		Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Skin (rabbit):20 mg/24hr-moderate	
	Skin (rabbit):400 mg (open)-mild	
	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
n-butanol	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 3400 mg/kg <sup>[2]</sup>	Eye (human): 50 ppm - irritant
	Inhalation (Rat) LC50: 8000 ppm4h <sup>[2]</sup>	Eye (rabbit): 1.6 mg-SEVERE
	Oral (Rat) LD50: 790 mg/kg <sup>[2]</sup>	Eye (rabbit): 24 mg/24h-SEVERE
	Eye: adverse effect observed (irreversible damage) <sup>[1]</sup>	
	Skin (rabbit): 405 mg/24h-moderate	
	Skin: adverse effect observed (irritating) <sup>[1]</sup>	
talc	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Inhalation (Rat) LC50: >2.1 mg/l4h <sup>[1]</sup>	Skin (human): 0.3 mg/3d-I mild
	Oral (Rat) LD50: >5000 mg/kg <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
N,N'-ethylenebisstearamide	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Oral (Rat) LD50: >2000 mg/kg <sup>[1]</sup>	Skin (rabbit) patch in PEG400 Non-irritant Mucous memb. (rabbit) in PEG 400 Slight irritant [Hoechst Australia]
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
di-sec-octyl phthalate	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (Guinea Pig) LD50: 10000 mg/kg <sup>[2]</sup>	Eye (rabbit): 500 mg/24h mild
	Inhalation (Rat) LC50: >10.62 mg/l4h <sup>[2]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>
	Oral (Mouse) LD50; 1500 mg/kg <sup>[2]</sup>	Skin (rabbit): 500 mg/24h mild
		Skin: adverse effect observed (irritating) <sup>[1]</sup>
urea formaldehyde resin, isobutylated	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: >5000 mg/kg <sup>[2]</sup>	Eye (rabbit): 0.1 ml/24 h-SEVERE

	Oral (Rat) LD50: >5000 mg/kg <sup>[2]</sup>	
formaldehyde.	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 270 mg/kg <sup>[2]</sup>	Eye (human): 4 ppm/5m
	Inhalation (Rat) LC50: <463 ppm4h <sup>[1]</sup>	Eye (rabbit): 0.75 mg/24H SEVERE
	Oral (Rat) LD50: 100 mg/kg <sup>[2]</sup>	Skin (human): 0.15 mg/3d-I mild
		Skin (rabbit): 2 mg/24H SEVERE
		Skin: adverse effect observed (corrosive) <sup>[1]</sup>

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT	<p>Inhalation (rat) TCLo: 1320 ppm/6h/90D-I * [Devoe]</p> <p>Most Low Boiling Point Naphthas (LBPNS) have low acute toxicity to oral, dermal and inhalation routes of exposure, and mild to moderate skin and eye irritating effects. However, some heavier 'cracked' LBPNS (LKBPNS with greater olefinic content) have been found to be more irritating to the skin and eyes compared to non-cracked LBPNS.</p> <p>LBPNS are not known to be sensitising to the skin.</p> <p>Animal studies examined the effects of short-term and longer-term exposure to LBPNS through inhalation or oral routes. In male rats specifically, exposure to LBPNS resulted in kidney-related issues like increased kidney weight, kidney lesions, and hyaline droplet formation. However, the same effects were not seen in female rats, mice, or humans due to a mechanism of action involving a particular enzyme only found in male rats.</p> <p>Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins.</p> <p>The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species. In many cases, the hydrophobic hydrocarbons are ingested in association with fats in the diet. Some hydrocarbons may appear unchanged as in the lipoprotein particles in the gut lymph, but most hydrocarbons partly separate from fats and undergo metabolism in the gut cell.</p> <p>For trimethylbenzenes:</p> <p>Absorption of 1,2,4-trimethylbenzene occurs after exposure by swallowing, inhalation, or skin contact. In the workplace, inhalation and skin contact are the most important routes of absorption; whole-body toxic effects from skin absorption are unlikely to occur as the skin irritation caused by the chemical generally leads to quick removal. The substance is fat-soluble and may accumulate in fatty tissues. It is also bound to red blood cells in the bloodstream.</p> <p>For C9 aromatics (typically trimethylbenzenes – TMBs)</p> <p>Acute toxicity: Animal testing shows that semi-lethal concentrations and doses vary amongst this group. The semilethal concentrations for inhalation range from 6000 to 10000 mg/cubic metre for C9 aromatic naphtha and 18000-24000 mg/cubic metre for 1,2,4- and 1,3,5-TMB, respectively.</p> <p>Irritation and sensitization: Results from animal testing indicate that C9 aromatic hydrocarbon solvents are mildly to moderately irritating to the skin, minimally irritating to the eye, and have the potential to irritate the airway and cause depression of breathing rate. There is no evidence that it sensitizes skin.</p> <p>Repeated dose toxicity: Animal studies show that chronic inhalation toxicity for C9 aromatic hydrocarbon solvents is slight. Similarly, oral exposure does not appear to pose a high toxicity hazard for pure trimethylbenzene isomers.</p> <p>Mutation-causing ability: No evidence of mutation-causing ability and genetic toxicity was found in animal and laboratory testing.</p> <p>Reproductive and developmental toxicity: No definitive effects on reproduction were seen, although reduction in weight in developing animals may be seen at concentrations that are toxic to the mother.</p> <p>Petroleum contains aromatic (benzene, toluene, ethyl benzene, naphthalene) and aliphatic hydrocarbons (n-hexane), which can result in many detrimental health effects, including, cancer, tumour formation, hearing loss, and nervous system toxicity.</p> <p>Animal testing shows breathing in petroleum causes tumours of the liver and kidney; these are however not considered to be relevant in humans. Similarly, exposure to gasoline over a lifetime can cause kidney cancer in animals, but the relevance in humans is questionable. Most studies involving gasoline have shown that gasoline does not cause genetic mutation, including all recent studies in living human subjects (such as in petrol service station attendants).</p> <p>Animal studies show concentrations of toluene (&gt;0.1%) can cause developmental effects such as lower birth weight and developmental toxicity to the nervous system of the foetus. Other studies show no adverse effects on the foetus.</p> <p>Prolonged contact with petroleum may result in skin inflammation and make the skin more sensitive to irritation and penetration by other materials.</p>
	N-BUTYL ACETATE
ACETONE	<p>For acetone:</p> <p>The acute toxicity of acetone is low. Acetone is not a skin irritant or sensitizer, but it removes fat from the skin, and it also irritates the eye. Animal testing shows acetone may cause anaemia. Studies in humans have shown that exposure to acetone at a level of 2375 mg/m3 does not negatively impact an individual's emotional regulation, behaviour, or learning ability.</p>
XYLENE	Reproductive effector in rats
N-BUTANOL	<p>For n-butanol:</p> <p>Acute toxicity: In animal testing, n-butanol (BA) was only slightly toxic, following exposure by swallowing, skin contact or irritation. Animal testing and human experience suggest that n-butanol is moderately irritating to the skin but severely irritating to the eye. Human studies show that BA is not likely to cause skin sensitization. Warning of exposure occurs before irritation of the nose, because n-butanol has an odour which can be detected below concentration levels cause irritation.</p> <p>Repeat dose toxicity: Animal testing showed temporarily reduction in activity and food intake following repeated exposure to BA, but otherwise there was no evidence of chronic toxicity.</p> <p>Reproductive toxicity: Several animal studies indicate BA does not possess reproductive toxicity, and does not affect fertility.</p> <p>Developmental toxicity: BA only caused developmental changes and toxic effects on the foetus near or at levels that were toxic to the mother.</p> <p>Genetic toxicity: Testing shows that BA does not possess genetic toxicity.</p> <p>Cancer-causing potential: Based on negative results from testing for potential of n-butanol to cause mutations and chromosomal aberrations, BA has a very small potential for causing cancer.</p>

TALC	The overuse of talc in nursing infants has resulted in respiratory damage causing fluid in the lungs and lung inflammation which may lead to death within hours of inhalation. Long-term exposure can also cause a variety of respiratory symptoms.
N,N'-ETHYLENEBISSTEARAMIDE	Laboratory testing shows that the fatty acid amide, cocoamide DEA, causes occupational allergic contact dermatitis, and that allergy to this substance is becoming more common. Alkanolamides are manufactured by condensation of diethanolamine and the methyl ester of long chain fatty acids. The chemicals in the Fatty Nitrogen Derived (FND) Amides are generally similar in terms of physical and chemical properties, environmental fate and toxicity. Its low acute oral toxicity is well established across all subcategories by the available data and show no apparent organ specific toxicity, mutation, reproductive or developmental defects.
DI-SEC-OCTYL PHTHALATE	Oral (rat) NOAEL: 28.9-36.1 mg/kg/day Gastrointestinal changes, respiratory system changes, somnolence, haemorrhage, necrotic changes in GI tract, lowered blood pressure, liver, endocrine tumours, foetotoxicity, paternal effects, maternal effects, specific developmental abnormalities (hepatobiliary system, musculoskeletal system, cardiovascular system, urogenital system, central nervous system, eye/ear), foetoletality recorded. Di-sec-octyl phthalate (DEHP) in animal testing has not been shown to be acutely toxic when swallowed. Very high doses may cause reduced growth and increased liver and kidney weights. In animals, DEHP does not seem to affect fertility; however it may cause birth defects (notably of the bone) and mutations. Workers exposed to phthalate vapours have noted pain, numbness and limb spasms after years of exposure, with inflammation of nerves and poor balance. The material may produce peroxisome proliferation. Peroxisomes are single, membrane limited organelles in the cytoplasm that are found in the cells of animals, plants, fungi, and protozoa. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Available data indicate that phthalate esters are minimally toxic by swallowing, inhalation and skin contact. Repeated exposure may result in weight gain, liver enlargement and induction of liver enzymes. They may also cause shrinking of the testicles and other structural malformations. They may reduce male and female fertility and number of live births, according to animal testing. <b>NOTE:</b> Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA. <b>WARNING:</b> This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.
UREA FORMALDEHYDE RESIN, ISOBUTYLATED	for polymer Somnolence, dermatitis after systemic exposure recorded.
FORMALDEHYDE.	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration. <b>WARNING:</b> This substance has been classified by the IARC as Group 1: <b>CARCINOGENIC TO HUMANS.</b>
ETHYL ACETATE & N-BUTANOL & TALC & N,N'-ETHYLENEBISSTEARAMIDE & UREA FORMALDEHYDE RESIN, ISOBUTYLATED & FORMALDEHYDE.	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.
N-BUTYL ACETATE & XYLENE & N-BUTANOL & UREA FORMALDEHYDE RESIN, ISOBUTYLATED & FORMALDEHYDE.	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
N-BUTYL ACETATE & ACETONE & XYLENE & ETHANOL & N-BUTANOL & DI-SEC-OCTYL PHTHALATE & UREA FORMALDEHYDE RESIN, ISOBUTYLATED	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
NITROCELLULOSE & TALC	No significant acute toxicological data identified in literature search.
XYLENE & TALC	The substance is classified by IARC as Group 3: <b>NOT</b> classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
DI-SEC-OCTYL PHTHALATE & FORMALDEHYDE.	Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen [National Toxicology Program: U.S. Dep. of Health & Human Services 2002]

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✓
Mutagenicity	✗	Aspiration Hazard	✗

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
✓ – Data available to make classification

## SECTION 12 Ecological information

### Toxicity

510-520 Traditional Pre Cat Lacquer	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
ethyl acetate	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	>75.6mg/l	2

Continued...

## 510-520 Traditional Pre Cat Lacquer

	EC50	72h	Algae or other aquatic plants	1800-3200mg/L	4
	EC50	48h	Crustacea	164mg/l	1
	NOEC(ECx)	72h	Algae or other aquatic plants	>100mg/l	1
	EC50	96h	Algae or other aquatic plants	2500mg/L	4
naphtha petroleum, light aromatic solvent	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	NOEC(ECx)	72h	Algae or other aquatic plants	1mg/l	1
	EC50	72h	Algae or other aquatic plants	19mg/l	1
	EC50	96h	Algae or other aquatic plants	64mg/l	2
	EC50	48h	Crustacea	6.14mg/l	1
n-butyl acetate	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	LC50	96h	Fish	17-19mg/L	4
	EC50	72h	Algae or other aquatic plants	246mg/l	2
	EC50	48h	Crustacea	32mg/l	1
	EC50(ECx)	96h	Fish	18mg/l	2
nitrocellulose	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	EC50(ECx)	96h	Algae or other aquatic plants	138-2400mg/L	4
	EC50	96h	Algae or other aquatic plants	138-2400mg/L	4
acetone	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	LC50	96h	Fish	3744.6-5000.7mg/L	4
	NOEC(ECx)	12h	Fish	0.001mg/L	4
	EC50	72h	Algae or other aquatic plants	5600-10000mg/L	4
	EC50	96h	Algae or other aquatic plants	9.873-27.684mg/l	4
	EC50	48h	Crustacea	6098.4mg/L	5
xylene	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	LC50	96h	Fish	2.6mg/l	2
	EC50	72h	Algae or other aquatic plants	4.6mg/l	2
	EC50	48h	Crustacea	1.8mg/l	2
	NOEC(ECx)	73h	Algae or other aquatic plants	0.44mg/l	2
ethanol	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	LC50	96h	Fish	42mg/L	4
	EC50(ECx)	96h	Algae or other aquatic plants	<0.001mg/L	4
	EC50	72h	Algae or other aquatic plants	275mg/l	2
	EC50	96h	Algae or other aquatic plants	<0.001mg/L	4
	EC50	48h	Crustacea	2mg/L	4
n-butanol	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	NOEC(ECx)	504h	Crustacea	4.1mg/l	2
	EC50	72h	Algae or other aquatic plants	>500mg/l	1
	EC50	96h	Algae or other aquatic plants	225mg/l	2
	EC50	48h	Crustacea	>500mg/l	1
	LC50	96h	Fish	100-500mg/l	4
talc	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	LC50	96h	Fish	89581.016mg/l	2
	NOEC(ECx)	720h	Algae or other aquatic plants	918.089mg/l	2
	EC50	96h	Algae or other aquatic plants	7202.7mg/l	2
N,N'-ethylenebisstearamide	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	LC50	96h	Fish	>1000mg/l	Not Available
	EC50	48h	Crustacea	>0.002mg/l	2
	BCF	1008h	Fish	<0.7	7
	EC50	72h	Algae or other aquatic plants	>0.053mg/l	2
	NOEC(ECx)	720h	Fish	<0.001mg/L	2

Continued...

## 510-520 Traditional Pre Cat Lacquer

	Endpoint	Test Duration (hr)	Species	Value	Source
	di-sec-octyl phthalate	ErC50	72h	Algae or other aquatic plants	>130mg/l
LC50		96h	Fish	>0.16mg/l	2
BCF		1344h	Fish	<0.7-29.7	7
EC50		72h	Algae or other aquatic plants	>130mg/l	1
EC50		48h	Crustacea	>0.16mg/l	1
NOEC(ECx)		1680h	Fish	0.007mg/l	1
EC50		96h	Algae or other aquatic plants	>0.1mg/l	1
urea formaldehyde resin, isobutylated	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
formaldehyde.	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	96h	Algae or other aquatic plants	0.005mg/l	4
	EC50	72h	Algae or other aquatic plants	1.034-1.984mg/l	4
	EC50	96h	Algae or other aquatic plants	0.375-0.579mg/l	4
	EC50	48h	Crustacea	3.26mg/l	4
	LC50	96h	Fish	0.727-9.193mg/L	4
<b>Legend:</b>	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**DO NOT discharge into sewer or waterways.**

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethyl acetate	LOW (Half-life = 14 days)	LOW (Half-life = 14.71 days)
n-butyl acetate	LOW	LOW
acetone	LOW (Half-life = 14 days)	MEDIUM (Half-life = 116.25 days)
xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
n-butanol	LOW (Half-life = 54 days)	LOW (Half-life = 3.65 days)
N,N'-ethylenebisstearamide	HIGH	HIGH
di-sec-octyl phthalate	HIGH (Half-life = 389 days)	LOW (Half-life = 1.21 days)
formaldehyde.	LOW (Half-life = 14 days)	LOW (Half-life = 2.97 days)

#### Bioaccumulative potential

Ingredient	Bioaccumulation
ethyl acetate	HIGH (BCF = 3300)
n-butyl acetate	LOW (BCF = 14)
acetone	LOW (BCF = 0.69)
xylene	MEDIUM (BCF = 740)
ethanol	LOW (LogKOW = -0.31)
n-butanol	LOW (BCF = 0.64)
N,N'-ethylenebisstearamide	LOW (BCF = 6.2)
di-sec-octyl phthalate	HIGH (BCF = 24500)
formaldehyde.	LOW (LogKOW = 0.35)

#### Mobility in soil

Ingredient	Mobility
ethyl acetate	LOW (Log KOC = 6.131)
n-butyl acetate	LOW (Log KOC = 20.86)
acetone	HIGH (Log KOC = 1.981)
ethanol	HIGH (Log KOC = 1)
n-butanol	MEDIUM (Log KOC = 2.443)
N,N'-ethylenebisstearamide	LOW (Log KOC = 5754000000)
di-sec-octyl phthalate	LOW (Log KOC = 165400)
formaldehyde.	HIGH (Log KOC = 1)

### SECTION 13 Disposal considerations

## Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>▶ Decontaminate empty containers.</li> </ul>
------------------------------	--

## SECTION 14 Transport information

## Labels Required

	
Marine Pollutant	NO
HAZCHEM	•3YE

## Land transport (ADG)

14.1. UN number or ID number	1263	
14.2. UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)	
14.3. Transport hazard class(es)	Class	3
	Subsidiary Hazard	Not Applicable
14.4. Packing group	II	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	Special provisions	163 367
	Limited quantity	5 L

## Air transport (ICAO-IATA / DGR)

14.1. UN number	1263	
14.2. UN proper shipping name	Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)	
14.3. Transport hazard class(es)	ICAO/IATA Class	3
	ICAO / IATA Subsidiary Hazard	Not Applicable
	ERG Code	3L
14.4. Packing group	II	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	Special provisions	A3 A72 A192
	Cargo Only Packing Instructions	364
	Cargo Only Maximum Qty / Pack	60 L
	Passenger and Cargo Packing Instructions	353
	Passenger and Cargo Maximum Qty / Pack	5 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y341
	Passenger and Cargo Limited Maximum Qty / Pack	1 L

## Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1263	
14.2. UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)	
14.3. Transport hazard class(es)	IMDG Class	3
	IMDG Subsidiary Hazard	Not Applicable
14.4. Packing group	II	
14.5. Environmental hazard	Not Applicable	

14.6. Special precautions for user	EMS Number	F-E , S-E
	Special provisions	163 367
	Limited Quantities	5 L

**14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code**

Product name	Group
ethyl acetate	Not Available
naphtha petroleum, light aromatic solvent	Not Available
n-butyl acetate	Not Available
nitrocellulose	Not Available
acetone	Not Available
xylene	Not Available
ethanol	Not Available
n-butanol	Not Available
talc	Not Available
N,N'-ethylenebisstearamide	Not Available
di-sec-octyl phthalate	Not Available
urea formaldehyde resin, isobutylated	Not Available
formaldehyde.	Not Available

**14.7.3. Transport in bulk in accordance with the IGC Code**

Product name	Ship Type
ethyl acetate	Not Available
naphtha petroleum, light aromatic solvent	Not Available
n-butyl acetate	Not Available
nitrocellulose	Not Available
acetone	Not Available
xylene	Not Available
ethanol	Not Available
n-butanol	Not Available
talc	Not Available
N,N'-ethylenebisstearamide	Not Available
di-sec-octyl phthalate	Not Available
urea formaldehyde resin, isobutylated	Not Available
formaldehyde.	Not Available

**SECTION 15 Regulatory information****Safety, health and environmental regulations / legislation specific for the substance or mixture****ethyl acetate is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australian Inventory of Industrial Chemicals (AIIC)

**naphtha petroleum, light aromatic solvent is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australian Inventory of Industrial Chemicals (AIIC)  
 Chemical Footprint Project - Chemicals of High Concern List  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

**n-butyl acetate is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australian Inventory of Industrial Chemicals (AIIC)

**nitrocellulose is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australian Inventory of Industrial Chemicals (AIIC)  
 International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

**acetone is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

## Australian Inventory of Industrial Chemicals (AIIC)

**xylene is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

**ethanol is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

**n-butanol is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

**talc is found on the following regulatory lists**

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

**N,N'-ethylenebisstearamide is found on the following regulatory lists**

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

**di-sec-octyl phthalate is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

**urea formaldehyde resin, isobutylated is found on the following regulatory lists**

Australian Inventory of Industrial Chemicals (AIIC)

**formaldehyde. is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 2

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

**Additional Regulatory Information**

Not Applicable

**National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (ethyl acetate; naphtha petroleum, light aromatic solvent; n-butyl acetate; nitrocellulose; acetone; xylene; ethanol; n-butanol; talc; N,N'-ethylenebisstearamide; di-sec-octyl phthalate; urea formaldehyde resin, isobutylated; formaldehyde.)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (nitrocellulose; urea formaldehyde resin, isobutylated)
Japan - ENCS	No (talc; urea formaldehyde resin, isobutylated)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (urea formaldehyde resin, isobutylated)
Vietnam - NCI	Yes
Russia - FBEPH	No (urea formaldehyde resin, isobutylated)
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

**SECTION 16 Other information**

Revision Date

31/05/2024

Continued...

